



A++



Inverter



Wi-Fi
Optional



Refrigerant
Gas



CE Marking



Regulation
2002/95/EC

| MODEL | | MTXT30HP24X | |
|--|-------------------------------------|------------------------------|-----------------------------------|
| Cooling | Nominal capacity (min-max) | Btu/h | 27000 (10850-28000) |
| | Nominal capacity (min-max) | W | 7920 (3180-8210) |
| | Absorbed electrical power (min-max) | W | 2450 (290-3100) |
| | EER | | 3,23 |
| | Pdesignc | kW | 7,9 |
| | SEER | W/W | 6,1 |
| | Energy efficiency class | | A++ |
| Heating | Nominal capacity (min-max) | Btu/h | 28000 (7800-29000) |
| | Nominal capacity (min-max) | W | 8210 (2290-8500) |
| | Absorbed electrical power (min-max) | W | 2210 (370-2900) |
| | COP | | 3,71 |
| | Pdesignh (Average) | kW | 5,6 |
| | SCOP (Average) | W/W | 4,0 |
| | Energy efficiency class (Average) | | A+ |
| | Pdesignh (Warmer) | kW | 6,1 |
| | SCOP (Warmer) | W/W | 5,1 |
| Energy Efficiency Class (Warmer) | | A+++ | |
| INDOOR UNIT | | (2x) MTXI9HP24 | MTXI12HP24 |
| Power Supply | V-Ph-Hz | 220-240, 1, 50 | |
| Air flow (Hi / Mi / Lo) | m3/h | 466/360/325 | 540/430/314 |
| Sound pressure level (Hi / Mi / Lo / Si) | dB(A) | 38,5/32/25 | 40,5/34,5/25 |
| Sound power level (Hi) | dB(A) | 55,0 | |
| Dimensions (LxWxH) | mm | 805x194x285 | |
| Dimensions with packaging (LxWxH) | mm | 870x285x360 | |
| Net / Gross Weight | kg | 7,6/9,7 | |
| OUTDOOR UNIT | | MTXT030HP24X | |
| Power Supply | V-Ph-Hz | 220-240, 1, 50 | |
| Max. power consumption | W | 4100 | |
| Sound pressure level | dB(A) | 58,0 | |
| Sound power level | dB(A) | 68,0 | |
| Dimensions (LxWxH) | mm | 890x342x673 | |
| Dimensions with packaging (LxWxH) | mm | 1030x438x750 | |
| Net / Gross Weight | kg | 48,0/51,8 | |
| REFRIGERANT DATA | | | |
| Refrigerant | Type | | R32 |
| | GWP | | 675 |
| | Refrigerant charge | kg | 1,85 |
| Refrigerant Pipe | Liquid / Gas | mm(inch) | 3xΦ6,35(3x1/4") / 3xΦ9,52(3x3/8") |
| | Max refrigeration line length | m | 30 |
| | Max altitude difference | m | 20 |
| | Refrigerant pre-charge | m | 5 |
| | Additional FGAS | g/m | 12 |
| | Operating temperature | Internal (cooling / heating) | °C |
| External (cooling / heating) | | °C | -15~50/-15~24 |