



* values being updated

A++



Inverter



Wi-Fi
Optional



Refrigerant
Gas



CE Marking



Regulation
2002/95/EC

MXX12HP24

Power Supply	V-Ph-Hz	230 - 1 - 50
Cooling capacity	W	3520 (1520 - 5230)
Cooling capacity	BTU/h	12000 (5200 - 18000)
Electric power absorbed in cooling mode	W	850 (350 - 1600)
EER		4,14
SEER		7,8
Energy efficiency class in cooling mode		A++
Heating capacity	W	4400 (1030 - 5570)
Heating capacity	BTU/h	15000 (3500 - 19000)
Electric power absorbed in heating	W	1100 (310 - 1800)
COP		4,00
SCOP Average		4,6
Energy efficiency class in heating mode Average*		A++
SCOP Warmer		5,1
Energy efficiency class in heating mode Warmer		A+++
Max. power consumption	W	2350
Current calculated in cooling mode	A	3,8 (1,6 - 7,1)
Current calculated in heating mode	A	5,0 (1,4 - 7,9)
Max. current	A	10,0
Indoor unit sound pressure level (Hi / Mi / Lo)	dB(A)	41/36/33
Indoor unit max sound power level	dB(A)	51,0
Outdoor unit sound pressure level	dB(A)	55,5
Outdoor unit sound power level	dB(A)	63,0
Indoor unit air flow (Hi / Mi / Lo)	m ³ /h	617/504/416
Indoor Unit Dimensions (LxWxH)	mm	570x570x260
Outdoor Unit Dimensions (WxDxH)	mm	800x333x554
Indoor Unit Net / Gross Weight	kg	16,2/21,4
Outdoor Unit Net / Gross Weight	kg	34,7/37,5
Type of refrigerant - GWP		R32 - 675
Refrigerant charge	kg	0,87
Refrigerant pipe diameter (Liquid-Gas)	inch	(1/4 - 3/8)
Max length of refrigeration line	m	25
Max height difference between Indoor Unit and Outdoor Unit	m	10
Type of compressor		ROTARY
Refrigerant pre-charge	m	5