



\* values being updated

**A++**



Inverter



Wi-Fi  
Optional



Refrigerant  
Gas



CE Marking



Regulation  
2002/95/EC

		<b>MXX18HP24</b>
Power Supply	V-Ph-Hz	230 - 1 - 50
Cooling capacity	W	5280 (2900 - 5740)
Cooling capacity	BTU/h	18000 (9900 - 19600)
Electric power absorbed in cooling mode	W	1633 (720 - 1860)
EER		3,23
SEER		6,1
Energy efficiency class in cooling mode		A++
Heating capacity	W	5420 (2370 - 6100)
Heating capacity	BTU/h	18500 (8100 - 20800)
Electric power absorbed in heating	W	1460 (700 - 1930)
COP		3,71
SCOP Average		4,0
Energy efficiency class in heating mode Average*		A+
SCOP Warmer		4,9
Energy efficiency class in heating mode Warmer		A++
Max. power consumption	W	2950
Current calculated in cooling mode	A	7,2 (3,2 - 8,2)
Current calculated in heating mode	A	6,4(3,1 - 8,5)
Max. current	A	13,5
Indoor unit sound pressure level (Hi / Mi / Lo)	dB(A)	42,5/39/35,5
Indoor unit max sound power level	dB(A)	56,0
Outdoor unit sound pressure level	dB(A)	55,0
Outdoor unit sound power level	dB(A)	63,0
Indoor unit air flow (Hi / Mi / Lo)	m <sup>3</sup> /h	720/625/540
Indoor Unit Dimensions (LxWxH)	mm	570x570x260
Outdoor Unit Dimensions (WxDxH)	mm	800x333x554
Indoor Unit Net / Gross Weight	kg	16,2/21,4
Outdoor Unit Net / Gross Weight	kg	34,7/37,5
Type of refrigerant - GWP		R32 - 675
Refrigerant charge	kg	1,15
Refrigerant pipe diameter (Liquid-Gas)	inch	(1/4 - 1/2)
Max length of refrigeration line	m	30
Max height difference between Indoor Unit and Outdoor Unit	m	20
Type of compressor		ROTARY
Refrigerant pre-charge	m	5