



A++



Inverter



Wi-Fi
Optional



Refrigerant
Gas



CE Marking



Regulation
2002/95/EC

MNX36HP24

Power Supply	V-Ph-Hz	230 - 1 - 50
Cooling capacity	W	10550 (4040 - 12020)
Cooling capacity	BTU/h	36000 (13800 - 41000)
Electric power absorbed in cooling mode	W	4000 (902 - 4900)
EER		2,63
SEER		6,1
Energy efficiency class in cooling mode *		A++
Heating capacity	W	11140 (2810 - 13190)
Heating capacity	BTU/h	38000 (9580 - 45000)
Electric power absorbed in heating	W	3100 (800 - 4640)
COP		3,60
SCOP Average		4,0
Energy efficiency class in heating mode Average		A+
SCOP Warmer		5,1
Energy efficiency class in heating mode Warmer		A+++
Max. power consumption	W	4700
Current calculated in cooling mode	A	17,5 (4,2 - 19,6)
Current calculated in heating mode	A	12,9 (3,6 - 18,4)
Max. current	A	21,5
Indoor unit sound pressure level (Hi / Mi / Lo)	dB(A)	47/43/40
Indoor unit max sound power level	dB(A)	63,0
Outdoor unit sound pressure level	dB(A)	65,0
Outdoor unit sound power level	dB(A)	67,0
Indoor unit air flow (Hi / Mi / Lo)	m ³ /h	1400/1150/750
Indoor Unit Dimensions (LxWxH)	mm	1360x774x249
Outdoor Unit Dimensions (WxDxH)	mm	946x410x810
Indoor Unit Net / Gross Weight	kg	40,5/48,5
Outdoor Unit Net / Gross Weight	kg	66,8/73,4
Type of refrigerant - GWP		R32 - 675
Refrigerant charge	kg	2,4
Refrigerant pipe diameter (Liquid-Gas)	inch	(3/8 - 5/8)
Max length of refrigeration line	m	65
Max height difference between Indoor Unit and Outdoor Unit	m	30
Type of compressor		ROTARY
Refrigerant pre-charge	m	5